

## MATERIAL SAFETY DATA SHEET

According to applicable EC directive

Product Name : BAYCOTECH-PRIMER 1K

Print Date : 02.01.2021

Version : 02

### 1- DEFINITION OF THE MATERIAL

**Product Name** : Baycotech-Primer 1K  
**Product Use** : Polyurethane based primer

**Manufacturer / supplier** : AB-SCHOMBURG YAPI KIMYASALLARI A.Ş.  
Address: 19 Mayıs Mah. Turapoğlu Sok. Hamdiye Yazgan İş Merkezi 4/8  
34736 – Kozyatağı / İstanbul / TURKEY  
Tel : +90 216 302 71 31  
Fax : +90 216 302 70 01  
info@ab-schomburg.com.tr  
[www.ab-schomburg.com.tr](http://www.ab-schomburg.com.tr)  
e-mail :  
web :

### 2- INFORMATION ABOUT COMPOSITION

Aromatic polyisocyanate solution

Diisocyanatotoluene (mixture of isomers) Weight -%: 0.1-0.5  
CAS No: 26471-62-5 (584-84-9/ 91-08-7) Index: Xn  
Index No: 615-006-00-4 R-Phrases: 20-42

Xylene Isomers mixture Weight -%: 10-25  
CAS – No: 1330-20-7 Index: Xn  
Index No: 601-022-00-9 R-Phrases: 20/21

n-Butyl acetate Weight-%: 0.5-2.5  
CAS No: 123-8-4  
Index No: 607-025-00-1 R-Phrases: 10, 66, 67

Aerosil 200 Weight-%: 0.5-2.5  
CAS No: 67762-90-7

### 3- HAZARD IDENTIFICATION

#### General

Flammable. Contains Isocyanates. See information supplied by manufacturer. Only for professional use.

## ***MATERIAL SAFETY DATA SHEET***

### **Skin Hazards**

Harmful by contact with skin.

### **Eye Hazards**

Causes eye irritation

**Inhalation Hazards** May cause sensitisation by inhalation.

For their own protection, persons who suffer from hypersensitivity of the respiratory tract (e.g. asthmatics and chronic bronchitis sufferer) should avoid handling this product.

1/5

*According*

*to applicable EC directive*

Product Name : BAYCOTECH-PRIMER 1K

Print Date : 02.01.2021  
Version : 02

---

## **4- FIRST AID CRITERIA**

### **General**

Take off immediately all contaminated clothing.

### **Inhalation**

If aerosol or vapour is inhaled in high concentrations, take the person into the fresh air and keep him warm, let him rest: if there is difficulty in breathing, medical advice is required.

### **Skin contact**

After contact with skin, wash immediately with plenty of water and soap.

### **Eye contact**

Contamination of the eyes must be treated by thorough irrigation with water, with the eyelids open. A doctor should be consulted immediately.

### **Swallowing**

Do not induce the patient to vomit, seek medical advice.

---

## **5- FIRE FIGHTING MEASURES**

Extinguishing media: CO<sub>2</sub>, foam, dry powder.

In cases of larger fires, water spray should be used.

Further information: In case of fire, formation of carbon monoxide, nitrogen oxide, amines, isocyanate vapour, and traces of hydrogen cyanide is possible. Fire men have to wear self-containing breather apparatus.,

---

## **6- ACCIDENTAL RELEASE MEASURES**

Put on protective equipment.

Do not empty into drains.

Remove mechanically. Cover remains with damp, fluid-binding material (sand, sawdust, chemical binder

# MATERIAL SAFETY DATA SHEET

based on calcium silicate hydrate). Transfer to waste container after approx. 1 hour and do not seal (CO<sub>2</sub> formation). Keep damp and in the open air in a safe place for 7 to 14 days. Waste should be disposed of as described in: Advice on Disposal”.

## 7- HANDLING AND STORAGE

**Storage:** Keep container tightly closed and dry. Avoid exposure to temperatures above 40 °C and below 5°C. Keep away from foodstuffs, drinks and tobacco.

**Handling:** Keep away from fire sources. Do not smoke.

Observe the usual precautionary measures for chemicals.

Precautions should generally be taken against electrostatic charges according to the equipment used and the way the product is handled and packed.

Ensure efficient ventilation. In all areas where products, like aerosols and /or vapour concentrations, are produced, exhaust ventilation must be provided. The air should be drawn away from the personnel handling the product, and the efficiency of the exhaust equipment should be periodically checked.

Explosion protection not required.

2/5

According

to applicable EC directive

Product Name : BAYCOTECH-PRIMER 1K

Print Date : 02.01.2021

Version : 02

## 8- EXPOSURE CONTROLS / PERSONAL PROTECTION

2,4/2,6-di-isocyanatotoluene: 0.005 ml/m<sup>3</sup> (ppm) corresp. to 0.035 mg/m<sup>3</sup> (eight hours average value)

CAS No: 584-84-9/91-08-7 Maximum limit of excess factor 4

Remark: 35, 36

Xylene (all isomers): 100 ml/m<sup>3</sup> (ppm) corresp. to 440 mg/m<sup>3</sup> (eight hours average value)

CAS No: 1330-20-7 Maximum limit of excess factor 4

Remark: H (=can be absorbed through the skin), DFG

n-Butyl acetate: 100 ml/m<sup>3</sup> (ppm) corresp. to 480 mg/m<sup>3</sup> (eight hours average value)

CAS No:123-86-4 Maximum limit of excess factor 1

Remark: 37, DFG

For technical protective measures to limit exposure see also " Handling and storage".

**Respiratory protection:** Respiratory protection is required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work a charcoal or A2-P2 filter is recommended.

**Hand protection:** Protective gloves for chemicals made out of fluorinated or butyl rubber.

**Eye protection:** Goggles/face protection.

## ***MATERIAL SAFETY DATA SHEET***

**Body protection:** Protective clothing.

Keep away from foodstuffs, drinks and tobacco. Keep working clothes separate. Wash hands before breaks and at end of work. Take off immediately all contaminated clothing.

### **9- PHYSICAL AND CHEMICAL PROPERTIES**

#### **General Information**

<b>Form:</b>	Viscous liquid
<b>Colour:</b>	White, terracotta-red, green, grey, black, etc
<b>Odour:</b>	Smell of solvent
<b>Setting point:</b>	<0°C
<b>Ignition temperature:</b>	>200°C
<b>Flash Point:</b>	>25°C
<b>Viscosity at 23 °C:</b>	>90 s, according ISO 2431:1993 with 6mm nozzle
<b>Solvent Separation:</b>	<3%, according UN Manual of Tests and Criteria, Section III, 32.5.1
<b>Density:</b>	1.37-1.46 g/ml (depending on colour)
<b>Solubility in water:</b>	insoluble reacts as described in Paragraph 10
<b>Explosion limits:</b>	Liquid product is not explosion dangerous, but explosive air/vapour mixtures can be formed

### **10- STABILITY AND REACTIVITY**

Hazardous decomposition products: No hazardous decomposition products when stored and handled correctly.

Hazardous reactions: Exothermic reaction with amines and alcohols; reacts with water forming CO<sub>2</sub>, inclosed containers risk of bursting owing to increase of pressure.

## ***MATERIAL SAFETY DATA SHEET***

*According to applicable EC directive*

Product Name : BAYCOTECH-PRIMER-1K

Print Date : 02.01.2021  
Version : 02

---

### **11- TOXICOLOGICAL INFORMATION**

Acute toxicity: LD50 oral, rat:>5000mg/kg

Effects on the eyes: Causes slight temporary reddening and swelling of the conjunctiva and slight reversible clouding of the cornea.

Effects on the skin: In case of longer contact with skin, tanning and irritating effects are possible.

Effect on the respiratory organs: Aromatic hydrocarbons, as xylene, irritate the skin and mucous membranes and are narcotic if inhaled in high concentrations.

Delayed appearance of the symptoms and allergic reaction in susceptible persons possible.

---

### **12- ECOLOGICAL INFORMATION**

Immiscible in water. Reacts with water at the interface producing CO<sub>2</sub> and forming a solid and insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by water-soluble solvents. Previous experience shows that polyurea is inert and non-degradable.

---

### **13- DISPOSAL INFORMATION**

European Code of Waste Designation (European Waste Catalogue (EWC)):

080409 Liquid (not cured) - Adhesive and Sealants containing organic solvents or other dangerous substances.

080410 Solid (cured) - Adhesive and Sealants wastes, except these that fall under 080409.

Disposal: In accordance with international, national or local Residue Management Regulations.

After final product withdrawal, all residues must be removed from containers (drip-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and the hazard labels must be invalidated. Containers must be recycled in compliance with national legislation and environmental regulations.

---

### **14- TRANSPORTATION INFORMATION**

Transport only in accordance with ADR for road, RID of rail, IMDG for sea and ICAO/IATA for transport.

Landtransport ADR/RID and GGVS/GGVE

ADR/RID Class: NO GOODS OF CLASS 3

If capacity of receptacles more than 450 litres, then declared class 3,

31C.

Seatransport IMDG/GGVSee

IMDG/GGVSee Class: NO GOODS OF CLASS 3

If capacity of receptacles more than 450 litres, then declared class 3, 31C.

Airtransport ICAO-TI and IATA-DGR

ICAO/IATA Class: 3 No. 31C  
UN/ID No: 1866  
Warning sign: 3  
Packing Group: III  
Declaration for air shipment: RESIN SOLUTION  
Proper shipping name: 1866, RESIN SOLUTION

4/5

## **MATERIAL SAFETY DATA SHEET**

*According to applicable EC directive*

Product Name : BAYCOTECH-PRIMER-1K

Print Date : 02.01.2021  
Version : 02

---

### **15- REGULATORY INFORMATION**

Labeling in accordance with Annex I of directive 67/548/EEC and its amendments and adaptations:

Symbol: Xn, hazard description: harmful

Contains: Isocyanates, See information supplied by the manufacturer.

R10: Flammable

R20: Harmful by inhalation.

R21: Harmful at contact with skin

R42: May cause sensitisation by inhalation.

S23: Do not breathe vapour/spray.

S24: Avoid contact with skin.

S36/37/39: Wear suitable protective clothing, gloves and goggles.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S45: In case of accident or if you feel unwell, seek medical advice immediately.

(Show this label where possible) Warning symbols : none

Hazard sentences ( R ) : none

Caution recommendation ( S ) : none

---

### **16- OTHER INFORMATION**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---

AB-SCHOMBURG