

BAYCO-JOINT-TAPE-2000

60% elastic – watertight sealing tape

Description:

BAYCO-JOINT-TAPE-2000 is a 60% elastic, polypropylene based, polyurethane film modified and watertight sealing tape.

Areas of Application:

The product is used as a sealing tape to prevent water penetration and formation of cracks under ceramic tiles and between application layers of waterproofing materials. Besides, the product can be used at

- Vertical and horizontal joints,
- Water tanks,
- Swimming pools,
- Pipe mouths,
- Slab-parapet joint places,
- Foundation slab-concrete wall joint places,
- Cold joints,
- Sealing rod clearances,

to prevent water penetration and formation of cracks.

Use TEYAPLAST-2K or BAYCOSEAL-2K/M to fix sealing tape BAYCO-JOINT-TAPE-2000.

Properties/Advantages:

- Polypropylene based, polyurethane film modified reinforcement tape.
- Elastic. (% 60)
- It does not tear off.
- Watertight.
- Water vapor permeable.
- It is resistant to aggressive substances.
- It is resistant to temperatures between -20-+90°C.

Technical Data:

Color:	white
Thickness:	0,3 mm
Allowance of initial movement:	max. %30 of joint width
Tension strength:	composite gripping ≥ 0,5 N/mm ²
Toxicity:	none

Packaging:

12cm, 20cm, 1m width alternatives in 25m and 50m rolls.

Storage:

In dry and weather proof conditions, the product can be stored for at least 5 years.

Method of Application:

BAYCO-JOINT-TAPE-2000 is pressed on joints over surfaces that are treated with respective waterproofing materials. The Joint tape is to be applied on the surface, evenly placed without creasing. Then the product can be covered with waterproofing material. The edges of the Joint Tape are to be bonded with an overlap of at least 5 cm and with the waterproofing material, covering the complete surface without creasing. For designated areas requiring specialized care, e.g.: for inner and outer corners we recommend safe application with BAYCO-JOINT-TAPE-Corner pieces. Otherwise, the corner application shall be done with a special detail.

